

Features

- 10A switching capability
- Low height, only 12.5 mm
- The creepage distance between the coil and the contact with a dielectric withstanding voltage of 4kV is more than 8mm
- Products conforming to IEC60335-1 standard are available
- Various contact types are available
- A variety of sockets are available
- UL insulation system: Class F
- Through-hole reflow specification products are available
- Outline Dimensions:(28.6×10.3×12.3)mm



■ CHARACTERISTICS

Specifications	Item		
Contact Data	Contact arrangement		1A, 1B, 1C
	Contact resistance(initial)		≤100mΩ(6VDC 1A)
	Contact material		AgSnO ₂
Rated value	Rated load(Resistance load)		10A 250VAC
	Max.switching voltage		440VAC
	Max.switching current		10A
	Max.switching capacity		2500VA
	Min.allowing load		5VDC 100mA
Electrical performance	Insulation resistance(initial)		1000MΩ(500VDC)
	Dielectric strength (initial)	Between open contacts	1000VAC,1 min
		Between coil&contacts	5000VAC,1 min
	Operate time		≤10ms
	Release time		≤5ms
Mechanical performance	Shock resistance	Functional	98m/s ² (10G)
		Destructive	980m/s ² (100G)
	Vibration resistance		10Hz~55Hz 1.5mm DA
Endurance	Mechanical		1×10 ⁷ ops
	Electrical(Room temperature)		10A 250VAC 1×10 ⁵ ops(ON/OFF=1s/9s)
Operate condition	Ambient temperature		-40℃~85℃
	Humidity		5% to 90%
Termination			PCB
Unit weight			Approx.8g
Construction			Plastic sealed, Flux proofed

■ COIL DATA(23℃)

Nominal Voltage	Operate Voltage VDC	Release Voltage VDC	Rated Current (± 10%)	Coil Resistance (± 10%)	Nominal Power	Max Voltage
DC 5V	≤3.75	≥0.25	50mA	100Ω	250mW	DC 6.5V
DC 6V	≤4.50	≥0.30	41.7mA	144Ω		DC 7.8V
DC 9V	≤6.75	≥0.45	27.8mA	324Ω		DC 11.7V
DC 12V	≤9.00	≥0.60	20.8mA	576Ω		DC 15.6V
DC 18V	≤13.50	≥0.90	13.9mA	1296Ω		DC 23.4V
DC 24V	≤18.00	≥1.20	10.4mA	2304Ω		DC 31.2V
DC 48V	≤36.00	≥2.40	6.3mA	7680Ω	300mW	DC 62.4V
DC 60V	≤45.00	≥3.00	5.0mA	12000Ω		DC 78.0V

■ ORDERING INFORMATION

FH48 -1A 1 S T -XXX DC12V

- ① Type
- ② Contact arrangement(1):1A=1 open contacts, 1B=1 close contacts, 1C=1 switched contacts
- ③ PCB mounting:1=type 1, 2=type 2, 3=type 3
- ④ Construction(2):Nil=Flux proofed,S=Plastic sealed
- ⑤ Contact material (3):T=AgSnO₂
- ⑥ Customer special code:numbers or letters denote customer's requirements
- ⑦ Coil specification:DC5/6/9/12/18/24/48/60V

- (1) If need the contact arrangement is 1B,please contact with the salesman to ask for the outline dimensions,wiring diagram and PC board layout.
- (2) When used in clean environment(excluding H₂S,SO₂,NO₂,dust and other pollutants), it is recommended to choose the Flux proofed type;When used in unclean environment(contain H₂S,SO₂,NO₂,dust and other pollutants), it is recommended to choose the Plastic sealed.
- (3) Due to the high surge current of relay connection,we propose to use AgSnO₂ contacts.



■ OUTLINE DIMENSIONS,WIRING DIAGRAM AND PC BOARD LAYOUT(Unit:mm)

1A1

Outline Dimensions

Wiring Diagram
(Bottom view)


PCB Layout
(Bottom view)



■ OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT (Unit:mm)

1A2


Outline Dimensions



Wiring Diagram
(Bottom view)




PCB Layout
(Bottom view)



1A3


Outline Dimensions



Wiring Diagram
(Bottom view)




PCB Layout
(Bottom view)



1B3


Outline Dimensions



Wiring Diagram
(Bottom view)




PCB Layout
(Bottom view)



1C1


Outline Dimensions



Wiring Diagram
(Bottom view)



PCB Layout
(Bottom view)





■ OUTLINE DIMENSIONS,WIRING DIAGRAM AND PC BOARD LAYOUT(Unit:mm)

1C2

Outline Dimensions

Wiring Diagram
(Bottom view)

PCB Layout
(Bottom view)



Remark: (1) In case of no tolerance shown in outline dimension:outline dimension $\leq$ 1mm,tolerance should be $\pm$ 0.2mm;outline dimension $>$ 1mm and $<$ 5mm,tolerance should be $\pm$ 0.3mm;outline dimension $\geq$ 5mm,tolerance should be $\pm$ 0.5mm.


(2) The tolerance without indicating for PCB layout is always $\pm$ 0.1mm.

■ SAFETY APPROVAL RATINGS


Approval	File No.	Contact arrangement	Contact material	Approved ratings		
UL/C-UL	E475405	1A、1C(NO)	AgSnO ₂	8/10A	277/250/240/125/120VDC	85℃
		1B、1C(NC)	AgSnO ₂	8/10A	277/250/240/125/120VDC	85℃
TUV	R 50610371	1A、1C(NO)	AgSnO ₂	8/10A	277/250/240/125/120VDC	85℃
		1B、1C(NC)	AgSnO ₂	8/10A	277/250/240/125/120VDC	85℃
CQC	CQC23002412542	1A、1C(NO)	AgSnO ₂	8/10A	277/250VDC	85℃
		1B、1C(NC)	AgSnO ₂	8/10A	277/250VDC	85℃

■ PERFORMANCE CURVES

MAXIMUM SWITCHING POWER



ENDURANCE CURVE



■ NOTICE

- ① In order to maintain the initial performance parameters of the relay, please be careful not to drop the product;
- ② The specification is for reference only. Specifications subject to change without notice.